

12345678910

REV.

DESCRIPTION

DRAWN

DATE

see sheet one

Instruction Manual

A. Set up Nano SIM card

Step 1. Insert the card with angle in the snaps.

Step 2. Press another side until it fixes by the snaps.

Snap-1

Snap-2

Snap-3

Snap-4

B. Remove Nano SIM card

Press the back of the card to make it detach from the snaps.

C. Tray insert in connector

Fool-proofing beveled corner

Fool-proofing track

Tray front

Tray insert direction

Inappropriate way of inserting tray may cause irreversible damage.

This part is a connector only, it should be used together with Nano SIM Tray, P/N:

Temperature	P/N	Description
85°C	115U-T001	Card Tray, Used for Nano SIM Card Socket Push Push, Lock, PC+ABS, Black, Bag
105°C	115U-T007	Card Tray for 115U-A101/A110, Nano SIM, PBT black, Bag, L16.25
105°C	115U-T008	Card Tray for 115U-A101/A110, Nano SIM, PBT black, Bag, L18.25

UNLESS OTHERWISE SPECIFIED TOLERANCE

UNIT:	DECIMAL	LINEAR	ANGLES
mm	X.	±0.50	±5°
	X.X	±0.25	±3°
	X.XX	±0.12	±1°



ATTEND

www.attend.com.tw

DRAWN	Fros	2020/04/06	DRAWN NAME: Nano SIM Socket, 6 Pin, Tray-Push Push, G/F, Reel	
CHECKED	Tim	2020/04/06		
APPROVED	Ken	2020/04/06	PRODUCT NO. 115U-A101	
	SCALE 2.5/1	SHEET 3/4	SIZE A4	FILE NAME 115U-A101_B_5

12345678910

