




REV.	DESCRIPTION	DRAWN	DATE
1	INITIAL RELEASE	FROS	2025/12/29



SPECIFICATION:

- CONN.
Housing: PA, UL94-V0 black
Contact: Brass, G/F plated over nickel
Shell: Zinc alloy, nickel plated over all
Locking: PC, black
Locking Ring: Brass, nickel plated over all
Spring 1 & 2: Stainless steel
- Rated current (40°C): 4A
- Rated voltage: 250V
- Waterproof: IP67
- Operation temperature: -40°C to 85°C

7	GLAND NUT	Zinc alloy
6	GLAND CAGE	POM, white
5	GLAND	Silicone, black
4	BODY	Zinc alloy
3	SHIELD	NBR, black
2	ORING	NBR, black
1	CONN.	See note

NO.		PART NAME	DESCRIPTION
UNLESS OTHERWISE SPECIFIED TOLERANCE			
UNIT:	DECIMAL	LINEAR	ANGLES
	X.	±0.50	±5°
	X.X	±0.25	±3°
	X.XX	±0.12	±1°
DRAWN		Fros	2025/12/29
CHECKED		Tim	2025/12/29
APPROVED		Ken	2025/12/29
SCALE		1/1	SHEET 1/1
SIZE		A4	
DRAWN NAME:		M12 A-Code Plug for Cable, 4Pin Male Pins for Field Installable	
PRODUCT NO.		216A-04MF2	
FILE NAME		216A-04MF2_B_1	



www.attend.com.tw