


REV.	DESCRIPTION	DRAWN	DATE
1	Initial release	Fros	2025/05/08
2	Revised wire spec, open end	Fros	2025/06/19

NOTES:

1. All cable 100% testing, any open, mis-wiring, short & intermittent are not permitted
2. RoHS compliance



Conn.1

PIN ASSIGNMENT

Conn.1

- | | |
|---|--------|
| 1 | Red |
| 2 | Black |
| 3 | Orange |

4	xg	Over Mold, PVC 50P, Black, T/N:HY-HX-0302
3	xg	Inner Mold, PE, T/N:HY-HX-0301
2	1PC	CONN., M8-A Code 3Pin Male, P/N: 219A-03MO0
1	1PC	Cable, UL2464 #22AWG x 4C+AL PVC JACKET, OD:4.5, Black
NO. Q'ty		DESCRIPTION
UNLESS OTHERWISE SPECIFIED TOLERANCE		
UNIT:	1~10 ±1	>401 ±10
	11~30 ±2	ANGLE ±5°
mm	31~50 ±3	
	51~200 ±5	
DRAWN	Fros	2025/05/08
CHECKED	Allen	2025/05/08
APPROVED	Ken	2025/05/08
SCALE	1/1	SIZE A4
DRAWN NAME:		M8 A-code 3pin male to open end
CUSTOMER NO.		L=120 CM
PRODUCT NO.		M8-3P00-12001