



205B-SAN0-R  
1 2 3 4 5

1.Type  
S:SMT solder tail  
SMT board lock

2.Contact Plating  
A:Gold Flash

3.Shell Plating  
N: Nickel plated

4.0:Top mount

5.RoHS

NO.	NAME	(BOTTOM VIEW) FINISH	REMARK	QTY
1	HOUSING	NYLON PA9T G.F. WHITE		1
2	PIN TERM.	PHOS. BRONZE T:0.25 GOLD/TIN PLATED	Gold Flash NI40-60 ; TIN120	4
3	SHELL	BRASS T:0.3 NICKEL PLATED	NI80-120 u"	1

UNLESS OTHERWISE SPECIFIED TOLERANCE		
ANGLES	ANG.	±5°
LINEAR	0.	±0.3
	0.0	±0.25
	0.00	±0.20
SCALE	AS SHOWN	UNIT: mm
DRAWN	Willis	2012/09/05
CHECKED	Angel	2012/09/05
APPROVED	Ken	2012/09/05



www.attend.com.tw

△	Revise:								
△	Revise:								
△	Revise:								

DRAWN NAME:  
USB A Receptacle Top Mount SMD Type

PRODUCT NO. 205B-SAN0-R

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME
1			4			A4	1.0	205B-SAN0-R_B_2