


(COMPONENT SIDE)  
PCB LAYOUT

205E-S A N 0-R  
1 2 3 4

- 1.Type
- S:SMD type
- 2.Contact Plating
- A:Gold Flash
- 3.Shell Plating
- N:Nickel plating
- 4.Rohs

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	NYLON PA9T G.F	BLACK		1
2	CONTACT	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	Gold Flash; NI:40~60 u"; TIN:120 u" (100% pure Tin of lead free plating)	4
3	SHELL	BRASS T:0.3	NICKEL PLATED	NI:50u"MINIMUM.	1

						UNLESS OTHERWISE SPECIFIED TOLERANCE			 www.attend.com.tw		
ANGLES		ANG.		±5°		LINEAR		0. ±0.3			
		0.0		±0.25				0.00 ±0.20			
SCALE		AS SHOWN		UNIT: mm							
DRAWN		Willis		2012/08/03		DRAWN NAME:		USB B Receptacle Straight 180° SMD Type			
CHECKED		Angel		2012/08/03		APPROVED		Ken			
APPROVED		Ken		2012/08/03		PRODUCT NO.		205E-SAN0-R			
REV.	DESCRIPTION			DATE	REV.	DESCRIPTION			DATE		
1	INITIAL RELEASE			20120803							
SIZE		A4		REV.		2.0		FILE NAME		205E-SAN0-R_B_2	