




REV.	DESCRIPTION	DRAWN	DATE
1	INITIAL RELEASE	TIM	2018/10/16
2	ECR220421001	TIM	2022/04/21

SPECIFICATION:


1. Current Rating: 4A
2. Voltage Rating: 250V
3. Waterproof: IPX7
4. Operating temperature range: -40°C~+85°C




BODY



NUT




PANEL CUT-OUT




6	Epoxy	Black
5	ORING	EPDM, Black
4	NUT	Brass, Nickel plating
3	SHELL	Brass, Nickel plating
2	CONTACT	Brass, 10u" Gold plating under Nickel
1	HOUSING	PBT, UL94V-0, Black

NO.		PART NAME		DESCRIPTION	
UNLESS OTHERWISE SPECIFIED TOLERANCE				ATTEND WWW.ATTEND.COM.TW	
UNIT: m m	DECIMAL	LINEAR	ANGLES		
	X.	±0.50	±5°		
	X.X	±0.25	±3°		
	X.XX	±0.12	±1°		
DRAWN		Tim		2018/10/16	
CHECKED		Fros		2018/10/16	
APPROVED		Ken		2018/10/16	
		SCALE 2/1		SHEET 1/1	SIZE A4
FILE NAME				216A-03MAF_B_2	


1. Wire Processing



2. Installation Direction



3. Connector Mated to Panel Mount



UNLESS OTHERWISE SPECIFIED TOLERANCE				 ATTEND	
UNIT:	DECIMAL	LINEAR	ANGLES		
m m	X.	±0.50	±5°	WWW.ATTEND.COM.TW	
	X.X	±0.25	±3°		
	X.XX	±0.12	±1°		
DRAWN	Tim	2025/02/25	DRAWN NAME:		
CHECKED	Fros	2025/02/25	M Series For Male Solder Type Front Fastener Design Guide		
APPROVED	Ken	2025/02/25	PRODUCT NO.		
	SCALE	SHEET 1/1	SIZE A4	FILE NAME	M Series MAF_DG