


REV.	DESCRIPTION	DRAWN	DATE
1	Initial release	TIM	2025/08/07

NOTES:

1. All cable 100% testing, any open, mis-wiring, short & intermittent are not permitted
2. RoHS compliance
3. Characteristic impedance: 100 Ω
4. Operating temperature range: -40°C~+105°C



PIN ASSIGNMENT

Conn.1		Conn.2
1-1	————	1-1
1-2	————	1-2
2-1	————	2-1
2-2	————	2-2
3-1	————	3-1
3-2	————	3-2
4-1	————	4-1
4-2	————	4-2
Shield	————	Shield

2	2PCS	CONN., HS-MTP Straight Jack(2x2), Gold plated 30u"		
1	4PCS	Coaxial Cable, 26AWGx2C+AB, OD3.8, Black		
NO.	Q'ty	DESCRIPTION		
UNLESS OTHERWISE SPECIFIED TOLERANCE		ATTEND www.attend.com.tw		
UNIT:	1~10 ±1 11~30 ±2 31~50 ±3 51~200 ±5			>401 ±10 ANGLE ±5°
m m				
DRAWN	Tim	2025/08/07	DRAWN NAME:	
CHECKED	Fros	2025/08/07	HS-MTP Jack(2x2) to Jack(2x2) Cable L=100 CM, Z CODE	
APPROVED	Allen	2025/08/07	CUSTOMER NO.	
	SCALE 1.0	SHEET 1/1	SIZE A4	
PRODUCT NO.		MTP-1J1J-100Z03		