



RECOMMENDED LAYOUT (TOP VIEW)
GENERAL TOLERANCE: $\pm 0.05\text{mm}$

REV.	DESCRIPTION	DRAWN	DATE
1	INITIAL RELEASE	FROS	2015/04/13
2	Revised terminal width 0.45W -> 0.6W	TIM	2021/11/29

SPECIFICATION:

1. ELECTRICAL

1.1 Current Rating: 1.5A (USB Section)
3.0A (Powered Section)

1.2 Voltage Rating: USB: 5.25V DC, Powered: 5V

1.3 Contact Resistance: 40m Ω Max.

1.4 Insulation Resistance: 1000M Ω at 500V DC

1.5 Dielectric Withstanding Voltage: 750V AC

2. MECHANICAL

2.1 Durability: 1,500 Cycle

2.2 Mating Force: 67N max.

2.3 UN-Mating Force: 10N max.

3. ENVIRONMENTAL

3.1 Operating temperature range: -20 $^{\circ}\text{C}$ ~+85 $^{\circ}\text{C}$

3.2 Storage temperature range: -20 $^{\circ}\text{C}$ ~+85 $^{\circ}\text{C}$

4. SOLDER ABILITY

4.1 Recommend Temperature: 245 $^{\circ}\text{C}$

Contact Number	Signal Name	Plugging Sequence
Shell	Shield	1
1	VBUS	2
2	D-	3
3	D+	3
4	USB Ground	2
5	PWR Ground	2
6	VPLUS	3
7	VPLUS	3
8	PWR Ground	2

4	SHRAPNEL	PHOSPHOR BRONZE, 60u"~100u" NICKEL PLATED OVER ALL
3	SHELL	BRASS 0.3T, 60u"~100u" NICKEL PLATED OVER ALL
2	CONTACT	PHOSPHOR BRONZE 0.3T,
		CONTACT AREA: 30u" MIN. GOLD PLATED
		SOLDER AREA: MATTE-TIN , UNDER PLATED: 50u" MIN. NICKEL
1	Insulator	NYLON46 UL94V-0, BLACK COLOR

NO.	PART NAME	DESCRIPTION
-----	-----------	-------------

UNLESS OTHERWISE SPECIFIED TOLERANCE

UNIT:	DECIMAL	LINEAR	ANGLES
	mm	X.	± 0.50
	X.X	± 0.25	$\pm 3^{\circ}$
	X.XX	± 0.12	$\pm 1^{\circ}$



WWW.ATTEND.COM.TW

DRAWN	Fros	2015/04/13	DRAWN NAME:	Powered USB Socket
CHECKED	Zola	2015/04/13		5V, 30u" Gold, Black
APPROVED	Albert	2015/04/13	PRODUCT NO.	218B-5G01
SCALE	2/1	SHEET	1/1	SIZE
				A4
FILE NAME	218B-5G01_B_2			